



Industrial Automation Products & Solutions



Dold Insulation Monitoring Relay, 1, 3 Phase, DPDT, 0 → 500V ac, DIN Rail

ผู้ผลิต : Dold

รหัสสินค้า : MK5880N.12 AC50-400Hz 220-240V 5-100kOhm

Specifications

คุณลักษณะ	รายละเอียด
Monitoring Application	Insulation
Electrical Phase	1, 3
Contact Configuration	DPDT
Voltage Sensing Range	0 - 500V ac
Mounting Type	DIN Rail
Frequency Sensing Range	50 - 400Hz
Series	MK5880N
Terminal Type	Screw
Maximum Voltage Sensed	500V ac
Minimum Frequency Sensed	50Hz
Operating Temperature Range	+60°C
Dimensions	97 x 22.5 x 90mm
Minimum Voltage Sensed	0V ac
Length	97mm
Maximum Frequency Sensed	400Hz



บริษัท ทีเอส โซลูชัน จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Maximum Operating Temperature	+60°C
Width	22.5mm
Height	90mm
Minimum Operating Temperature	-20°C



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com