




Industrial Automation Products & Solutions



RS PRO PCB Mount Signal Relay, 5V dc Coil, 2A Switching Current, SPDT

ผู้ผลิต : RS PRO

รหัสสินค้า : 800-4524

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	5V dc
Contact Configuration	SPDT
Mounting Type	PCB Mount
Maximum Switching Current AC	2 A
Maximum Switching Current DC	2 A
Maximum Switching Voltage AC	250V
Maximum Switching Voltage DC	220V
Maximum Switching Power DC	60 W
Latching	No
Length	10mm
Depth	6.5mm
Height	5.65mm
Dimensions	10 x 5.65 x 6.5mm
Terminal Type	Through Hole
Switching Current	2A
Number of Poles	2
Application	Signal
Coil Power	140mW




บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Electrical Life	10 ⁵ Operations
Isolation Coil To Contact	1.6kV ac
Maximum Operating Temperature	+85°C
Minimum Operating Temperature	-40°C
Standards Met	cULus E133481, RoHS Compliant
Relay Switching Classification	Subminiature Signal Relay
Features	High Contact Capacity, Low Power Consumption
Operating Temperature Range	-40 - +85°C
Coil Resistance	178Î©
Maximum Switching Power AC	60VA
Life	100000 (Electrical) Operations, 100000000 (Mechanical) Operations
Contact Material	Gold Plated, Rhodium Plated Palladium Nickel



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com