



Industrial Automation Products & Solutions



RS PRO PCB Mount Signal Relay, 24V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : RS PRO

รหัสสินค้า : 800-4536

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	24V dc
Contact Configuration	DPDT
Mounting Type	PCB Mount
Maximum Switching Current AC	2 A
Maximum Switching Current DC	2 A
Maximum Switching Voltage AC	250V
Maximum Switching Voltage DC	220V
Series	Axicom P2
Maximum Switching Power DC	60 W
Latching	No
Length	10mm
Depth	6.5mm
Height	5.65mm
Dimensions	10 x 5.65 x 6.5mm
Terminal Type	Through Hole
Switching Current	2A
Number of Poles	2
Application	Signal



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Operating Temperature Range	-40 - +85°C
Coil Resistance	2800Î©
Maximum Switching Power AC	62.5VA
Coil Power	200mW
Life	100000 (Electrical) Operations, 100000000 (Mechanical) Operations
Isolation Coil To Contact	1.6kV ac
Features	High Contact Capacity, Low Power Consumption
Relay Switching Classification	Subminiature Signal Relay
Standards Met	cULus E133481, RoHS Compliant
Contact Material	Gold Plated
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	+85°C
Electrical Life	10^5 Operations



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com