




Industrial Automation Products & Solutions



TE Connectivity Surface Mount Signal Relay, 12V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : IM16GR

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	12V dc
Contact Configuration	DPDT
Mounting Type	Surface Mount
Maximum Switching Current DC	2 A
Maximum Switching Voltage AC	250V ac
Maximum Switching Voltage DC	220V dc
Maximum Switching Power DC	60 W
Series	IM
Length	10mm
Latching	No
Depth	6mm
Height	5.65mm
Dimensions	10 x 6 x 5.65mm
Terminal Type	Through Hole
Application	Signal
Number of Poles	2
Switching Current	2A
Contact Material	Gold Plated, Rhodium Plated Palladium Nickel



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Features	Bifurcated Contacts, Low Coil Power Consumption
Operating Temperature Range	-40 - +85°C
Coil Resistance	1.315 kΩ
Maximum Operating Temperature	+85°C
Coil Power	110mW
Minimum Operating Temperature	-40°C
Maximum Switching Power AC	62.5 VA



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com