




Industrial Automation Products & Solutions



Panasonic Surface Mount Signal Relay, 5V dc Coil, 3A Switching Current, SPST

ผู้ผลิต : Panasonic

รหัสสินค้า : DS1E-M-DC5V

Specifications

| คุณลักษณะ | รายละเอียด |
|------------------------------|---|
| Coil Voltage | 5V dc |
| Contact Configuration | SPST |
| Mounting Type | Surface Mount |
| Maximum Switching Current DC | 3 A |
| Maximum Switching Voltage AC | 250V ac |
| Maximum Switching Voltage DC | 220V dc |
| Maximum Switching Power DC | 60 W |
| Series | DS |
| Latching | No |
| Length | 20mm |
| Depth | 9.9mm |
| Height | 9.4mm |
| Dimensions | 20 x 9.9 x 9.9mm |
| Terminal Type | PCB Pin |
| Number of Poles | 1 |
| Application | General Purpose, Office Equipment, Safety, Telecommunications |
| Switching Current | 3A |
| Electrical Life | 5000000 Operation Cycles |




บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

| | |
|-------------------------------|---|
| Coil Power | 400mW |
| Operating Temperature Range | -40 - +70°C |
| Coil Resistance | 62.5Ω |
| Maximum Switching Power AC | 125VA |
| Life | 10 ⁷ (Mechanical) Operations, 5 x 10 ⁵ (Electrical) Operations |
| Minimum Operating Temperature | -40°C |
| Contact Material | Gold Plated |
| Isolation Coil To Contact | 1.5kV rms |
| Maximum Operating Temperature | +70°C |
| Features | Suitable For Use In Difficult Environments, Gold Clad Twin Contacts Ensure High Reliability, Can Be Used With Automatic Solder And Automatic Wash Systems |



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com