



Industrial Automation Products & Solutions



TE Connectivity PCB Mount Signal Relay, 24V dc Coil, 3A Switching Current, 6PDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : V23030C2021A106

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	24V dc
Contact Configuration	6PDT
Mounting Type	PCB Mount
Maximum Switching Current DC	3 A
Maximum Switching Voltage AC	250V
Maximum Switching Voltage DC	250V
Maximum Switching Power DC	60 W
Series	Card SN
Length	39.7mm
Latching	No
Depth	37.4mm
Height	10.2mm
Dimensions	39.7 x 37.4 x 10.2mm
Terminal Type	Surface Mount
Application	Signal
Number of Poles	6
Switching Current	3A
Isolation Coil To Contact	1.5kV rms



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Maximum Operating Temperature	+70°C
Contact Material	Gold Plated
Operating Temperature Range	-40 - +70°C
Features	Low Profile, Therefore Particularly Suited For Flat Pack Components Grouping
Maximum Switching Power AC	62.5VA
Minimum Operating Temperature	-40°C
Coil Power	789mW
Coil Resistance	730 Î©



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com