



Industrial Automation Products & Solutions



TE Connectivity PCB Mount Signal Relay, 24V dc Coil, 1.25A Switching Current, SPST

ผู้ผลิต : TE Connectivity

รหัสสินค้า : V23101D7B201

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	24V dc
Contact Configuration	SPST
Mounting Type	PCB Mount
Maximum Switching Current DC	1.25 A
Maximum Switching Voltage AC	125V ac
Maximum Switching Voltage DC	120V dc
Series	W11
Maximum Switching Power DC	30 W
Length	15.4mm
Latching	No
Depth	10mm
Height	11.5mm
Dimensions	15.4 x 11.5 x 10mm
Terminal Type	Through Hole
Number of Poles	1
Switching Current	1.25A
Application	Signal
Features	Multi Purpose Relay, Immersion Cleanable



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Coil Resistance	1.28 kΩ
Coil Power	450mW
Maximum Operating Temperature	+85°C
Minimum Operating Temperature	-40°C
Contact Material	Gold Plated
Operating Temperature Range	-40 - +85°C
Maximum Switching Power AC	60 VA
Isolation Coil To Contact	1kV rms
Life	10000000 (Electrical) cycles, 10000000 (Mechanical) cycles



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com