




Industrial Automation Products & Solutions



TE Connectivity PCB Mount Signal Relay, 24V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : V23079A1005B301

Specifications

| คุณลักษณะ | รายละเอียด |
|------------------------------|--------------------|
| Coil Voltage | 24V dc |
| Contact Configuration | DPDT |
| Mounting Type | PCB Mount |
| Maximum Switching Current DC | 2 A |
| Maximum Switching Voltage AC | 250V |
| Maximum Switching Voltage DC | 220V dc |
| Series | Axicom P2 |
| Maximum Switching Power DC | 60 W |
| Latching | No |
| Length | 14.5mm |
| Depth | 7.2mm |
| Height | 9.8mm |
| Dimensions | 14.5 x 9.8 x 7.2mm |
| Terminal Type | Through Hole |
| Number of Poles | 2 |
| Application | Signal |
| Switching Current | 2A |
| Maximum Switching Power AC | 62.5VA |



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

| | |
|-------------------------------|--|
| Isolation Coil To Contact | 2kV rms |
| Maximum Operating Temperature | +85°C |
| Coil Power | 140mW |
| Minimum Operating Temperature | -40°C |
| Contact Material | Gold Plated |
| Operating Temperature Range | -40 - +85°C |
| Coil Resistance | 4100Ω@ |
| Features | Bifurcated Contacts, Immersion cleanable |



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com