



Industrial Automation Products & Solutions



TE Connectivity Surface Mount Signal Relay, 12V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : D3403

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	12V dc
Contact Configuration	DPDT
Mounting Type	Surface Mount
Maximum Switching Voltage AC	250V
Maximum Switching Voltage DC	220V
Series	G6S
Maximum Switching Power DC	60 W
Latching	No
Length	15mm
Depth	7.5mm
Height	9.6mm
Switching Current	2A
Application	Communications Equipment, Consumer Electronics, Hi-Fi Products, ISDN, Linecard Application (Analogue), Measurement & Control Equipment, Medical Equipment, Office & Business Equipment, PABX, Set Top Boxes, Voice Over IP, xDSL
Number of Poles	2
Coil Power	140mW
Maximum Operating Temperature	+85°C



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Minimum Operating Temperature	-55°C
Isolation Coil To Contact	2kV ac
Relay Switching Classification	General Purpose Relay
Standards Met	UL 508 File No. E 111441
Contact Material	Palladium-Ruthenium
Coil Resistance	1028Ω@
Maximum Switching Power AC	62.5VA
Life	100000000 (Mechanical) operations, 2500000 (Electrical) operations



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com