



## Industrial Automation Products & Solutions



### Omron G3RV-ST Series Solid State Interface Relay, 110 V ac Control, 3 A Load, DIN Rail Mount

ผู้ผลิต : Omron

รหัสสินค้า : G3RV-ST700-D AC110

## Specifications

| คุณลักษณะ               | รายละเอียด |
|-------------------------|------------|
| Maximum Control Voltage | 110 V ac   |
| Maximum Load Current    | 3 A        |
| Mounting Type           | DIN Rail   |
| Maximum Load Voltage    | 26.4 Vdc   |
| Minimum Control Voltage | 88 V       |
| Control Voltage Range   | 88 - 121 V |
| Switching Type          | High-Speed |
| Contact Configuration   | SPDT       |
| Load Voltage Range      | 3 - 26.4V  |
| Minimum Load Voltage    | 3 Vdc      |
| Terminal Type           | Screw      |
| Number of Poles         | 1          |
| Input Current           | 6.7mA      |
| Width                   | 6.2mm      |
| Series                  | G3RV-ST    |
| Minimum Load Current    | 0.1 mA     |
| Length                  | 88mm       |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                          |
|-------------------------------|------------------------------------------|
| Rise Time                     | 6ms                                      |
| Height                        | 90mm                                     |
| Output Device                 | Photovoltage Coupler                     |
| Depth                         | 87.1mm                                   |
| Minimum Operating Temperature | -30°C                                    |
| Package Style                 | Carton Box                               |
| Off State Leakage Current     | 5 mA                                     |
| Isolation Voltage             | 2500V                                    |
| Range                         | G3RV                                     |
| Maximum Operating Temperature | +55°C                                    |
| Dimensions                    | 88 x 90 x 6.2mm                          |
| Standards Met                 | CSA C22.2 No.14, EN 62314, IEC 60529, UL |
| Special Features              | 60% Space Saving, Easy Maintenance       |
| Maximum Turn On Time          | 6 ms                                     |
| Manufacturer Part No.         | G3RV-ST700-D AC110                       |
| Operating Temperature Range   | -30 - 55°C                               |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com