




Industrial Automation Products & Solutions



Celduc SK Series Solid State Relay, 5 A Load, PCB Mount, 280 V ac Load, 10 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKB10420

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	5 A
Mounting Type	PCB Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	12 V ac
Maximum Control Voltage	10 V dc
Minimum Control Voltage	3 V dc
Switching Type	Zero Cross
Control Voltage Range	3 - 10 V dc
Range	SK
Minimum Load Current	1 mA
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Triac
Package Style	SIP4
Relay Type	AC
Series	SK
Load Voltage Range	12 - 280V ac
Maximum Turn On Time	10ms




บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	43.2 x 10.2 x 25.4mm
Maximum Operating Temperature	+100°C
Depth	10.2mm
Minimum Operating Temperature	-40°C
Standards Met	CE, VDE, EAC, cURus
Length	43.2mm
Operating Temperature Range	-40 - +100°C
Special Features	Zero Cross Solid State Relay for Printed Circuit Board designed for Resistive Loads, Lamps or Inductive Loads with External VDR, Very low leakage current
Off State Leakage Current	0.1 mA
Height	25.4mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com