



Industrial Automation Products & Solutions



Celduc SO8 Series Solid State Relay, 75 A Load, Panel Mount, 690 V ac Load, 32 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SO887060

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	75 A
Mounting Type	Panel Mount
Maximum Load Voltage	690 V ac
Minimum Load Voltage	24 V ac
Minimum Control Voltage	3.5 V dc
Maximum Control Voltage	32 V dc
Switching Type	Zero Cross
Control Voltage Range	3.5 - 32 V dc
Range	SO8
Minimum Load Current	5 mA
Number of Poles	1
Terminal Type	Screw
Output Device	Thyristor
Relay Type	AC
Series	SO8
Load Voltage Range	24 - 690V ac
Maximum Turn On Time	10ms



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	44.5 x 58.2 x 27mm
Depth	58.2mm
Height	27mm
Off State Leakage Current	1 mA
Operating Temperature Range	-40 - +100°C
Special Features	Zero Cross Solid State Relay Designed for Most Types of Loads, Very Low Zero Cross Voltage, Green LED Visualization on The Input
Standards Met	CE
Maximum Operating Temperature	+100°C
Minimum Operating Temperature	-40°C
Length	44.5mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com