



Industrial Automation Products & Solutions



Celduc SK Series Solid State Relay, 5 A Load, PCB Mount, 460 V ac Load, 30 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKA20441

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	5 A
Mounting Type	PCB Mount
Maximum Load Voltage	460 V ac
Minimum Load Voltage	12 V ac
Maximum Control Voltage	30 V dc
Minimum Control Voltage	4 V dc
Switching Type	Random
Control Voltage Range	4 - 30 V dc
Range	SK
Minimum Load Current	1 mA
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Triac
Package Style	SIP4
Relay Type	AC
Series	SK
Load Voltage Range	12 - 460V ac
Maximum Turn On Time	0.1ms




บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	43.2 x 10.2 x 25.4mm
Maximum Operating Temperature	+100°C
Depth	10.2mm
Length	43.2mm
Off State Leakage Current	0.1 mA
Operating Temperature Range	-40 - +100°C
Minimum Operating Temperature	-40°C
Special Features	Random Solid State Relay for Printed Circuit Board Designed for Most Types of Loads, Very Low Zero Cross Voltage, Very Low Leakage Current
Standards Met	CE, VDE, EAC, cURus
Height	25.4mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com