




Industrial Automation Products & Solutions



Celduc SK Series Solid State Relay, 10 A Load, PCB Mount, 600 V ac Load, 14 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKH10240

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	10 A
Mounting Type	PCB Mount
Maximum Load Voltage	600 V ac
Minimum Load Voltage	24 V ac
Maximum Control Voltage	14 V dc
Minimum Control Voltage	4 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 14 V dc
Minimum Load Current	5 mA
Range	SK
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Thyristor
Relay Type	AC
Package Style	SIP4
Load Voltage Range	24 - 600V ac
Series	SK



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Maximum Turn On Time	10ms
Dimensions	43.6 x 22 x 35.7mm
Maximum Operating Temperature	+80°C
Depth	22mm
Standards Met	CE, EAC, cURus
Operating Temperature Range	-40 - +80°C
Off State Leakage Current	1 mA
Height	35.7mm
Length	43.6mm
Special Features	Range for Printed Circuit Board with Integrated Heatsink, Zero-Cross AC Output, Thyristor and DCB Technology
Minimum Operating Temperature	-40°C



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com