



Industrial Automation Products & Solutions



Celduc SO9 Series Solid State Relay, 25 A Load, Panel Mount, 280 V ac Load, 30 V dc, 32 V ac Control

ผู้ผลิต : Celduc

รหัสสินค้า : SO942860

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	Panel Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	12 V ac
Minimum Control Voltage	10 V dc, 15 V ac
Maximum Control Voltage	30 V dc, 32 V ac
Switching Type	Zero Cross
Control Voltage Range	10 - 30 V dc, 15 - 32 V ac
Range	SO9
Minimum Load Current	5 mA
Number of Poles	1
Terminal Type	Screw
Output Device	Triac
Relay Type	AC
Series	SO9
Load Voltage Range	12 - 280V ac
Maximum Turn On Time	10ms



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	44.8 x 59.4 x 30mm
Maximum Operating Temperature	+100°C
Minimum Operating Temperature	-55°C
Standards Met	CE, EAC, cURus
Special Features	Zero Cross Solid State Relay Especially Designed for Resistive Loads, Green LED Visualization on The Input, IP20 Protection By Removable Flaps on Terminals with Optional Labels
Operating Temperature Range	-55 - +100°C
Length	44.8mm
Off State Leakage Current	1 mA
Height	30mm
Depth	59.4mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com