




## Industrial Automation Products & Solutions



# Celduc SK Series Solid State Relay, 25 A Load, PCB Mount, 600 V ac Load, 32 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKL20241

## Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	PCB Mount
Maximum Load Voltage	600 V ac
Minimum Load Voltage	24 V ac
Maximum Control Voltage	32 V dc
Minimum Control Voltage	8 V dc
Switching Type	Random
Control Voltage Range	8 - 32 V dc
Minimum Load Current	5 mA
Range	SK
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Thyristor
Package Style	SIP4
Relay Type	AC
Series	SK
Maximum Turn On Time	0.1ms



## บริษัท ทีเอส โซลูชัน จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Load Voltage Range	24 - 600V ac
Dimensions	43.4 x 6.3 x 24.5mm
Maximum Operating Temperature	+80°C
Minimum Operating Temperature	-40°C
Standards Met	cULus Recognized
Special Features	Range for Printed Circuit Board for Mounting on an External Heatsink, Zero-Cross AC Output, Thyristor DCB Technology
Operating Temperature Range	-40 - +80°C
Length	43.4mm
Off State Leakage Current	1 mA
Height	24.5mm
Depth	6.3mm



LINE OA  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com