



Industrial Automation Products & Solutions



Schneider Electric Harmony Relay Series Solid State Relay, 25 A Load, Panel Mount, 530 V ac Load, 32 V dc Control

ผู้ผลิต : Schneider Electric

รหัสสินค้า : SSP3A225BDR

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	Panel Mount
Maximum Load Voltage	530 V ac
Minimum Load Voltage	48 V ac
Maximum Control Voltage	32 V dc
Minimum Control Voltage	4 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 32 V dc
Minimum Load Current	0.1 A
Number of Poles	3
Terminal Type	Screw
Contact Configuration	3P-NO
Output Device	SCR
Relay Type	Three Channel Three Phase
Series	Harmony Relay
Maximum Turn On Time	8.33ms
Load Voltage Range	48 - 530V ac



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	101.3 x 97.8 x 35.5mm
Better World Product	Yes
Better World Verification	Green Premium
Capacitance	8pF
Standards Met	CE, CSA, UL
Special Features	For Robust Applications Requiring Considerable Heat Dissipation, SSP & SSRP Ranges Panel Mount Individually
Length	101.3mm
Off State Leakage Current	3 mA
Height	35.5mm
Operating Temperature Range	-40 - +80°C
Depth	97.8mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com