




Industrial Automation Products & Solutions



Celduc SK Series Solid State Relay, 50 A Load, PCB Mount, 690 V ac Load, 14 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKL10560

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	50 A
Mounting Type	PCB Mount
Maximum Load Voltage	690 V ac
Minimum Load Voltage	24 V ac
Minimum Control Voltage	4 V dc
Maximum Control Voltage	14 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 14 V dc
Range	SK
Minimum Load Current	5 mA
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Thyristor
Relay Type	AC
Package Style	SIP4
Series	SK
Maximum Turn On Time	10ms



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Load Voltage Range	24 - 690V ac
Dimensions	43.4 x 6.3 x 24.5mm
Standards Met	cULus Recognized
Height	24.5mm
Off State Leakage Current	1 mA
Length	43.4mm
Minimum Operating Temperature	-40°C
Operating Temperature Range	-40 - +80°C
Special Features	Range for Printed Circuit Board for Mounting on an External Heatsink, Zero-Cross AC Output, Thyristor DCB Technology
Maximum Operating Temperature	+80°C
Depth	6.3mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com