




## Industrial Automation Products & Solutions



# Celduc SK Series Solid State Relay, 25 A Load, PCB Mount, 280 V ac Load, 14 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SKL10220

## Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	PCB Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	12 V ac
Minimum Control Voltage	4 V dc
Maximum Control Voltage	14 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 14 V dc
Range	SK
Minimum Load Current	5 mA
Number of Poles	1
Terminal Type	PCB Pin
Output Device	Thyristor
Relay Type	AC
Package Style	SIP4
Load Voltage Range	12 - 280V ac
Series	SK



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Maximum Turn On Time	10ms
Dimensions	43.4 x 6.3 x 24.5mm
Maximum Operating Temperature	+80°C
Minimum Operating Temperature	-40°C
Depth	6.3mm
Height	24.5mm
Special Features	Range for Printed Circuit Board for Mounting on an External Heatsink, Zero-Cross AC Output, DCB Technology
Operating Temperature Range	-40 - +80°C
Standards Met	cULus Recognized
Off State Leakage Current	1 mA
Length	43.4mm



LINE OA  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com