



Industrial Automation Products & Solutions



i-Autoc KSI Series Solid State Relay, 25 A Load, Panel Mount, 530 V ac Load, 32 V dc Control

ผู้ผลิต : i-Autoc

รหัสสินค้า : KSI480D25-L

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	Panel Mount
Maximum Load Voltage	530 V ac
Minimum Load Voltage	48 V ac
Minimum Control Voltage	4 V dc
Maximum Control Voltage	32 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 32 V dc
Terminal Type	Screw
Output Device	SCR, TRIAC
Relay Type	Single Phase
Series	KSI
Maximum Turn On Time	10ms
Load Voltage Range	48 - 530V ac
Dimensions	58.4 x 45.7 x 20.5mm
Off State Leakage Current	5 mA
Minimum Operating Temperature	-30°C



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Operating Temperature Range	-30 - +80°C
Length	58.4mm
Height	20.5mm
Maximum Operating Temperature	+80°C
Standards Met	CCCs, CE, CULus, TUV
Depth	45.7mm
Special Features	Build-In MOV/TVS Option, DC Control, Dielectric Strength, LED Indicator, TRIAC or SCR Output



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com