



Industrial Automation Products & Solutions



Sensata Crydom CKR24 Series Solid State Relay, 20 A rms Load, DIN Rail Mount, 280 V rms Load, 32 V Control

ผู้ผลิต : Sensata / Crydom

รหัสสินค้า : CKRD2420

Specifications

| คุณลักษณะ | รายละเอียด |
|-------------------------|-------------|
| Maximum Load Current | 20 A rms |
| Mounting Type | DIN Rail |
| Maximum Load Voltage | 280 V rms |
| Minimum Load Voltage | 24 V rms |
| Minimum Control Voltage | 4 V ac/dc |
| Maximum Control Voltage | 32 V |
| Switching Type | Zero Cross |
| Control Voltage Range | 4 - 32 V dc |
| Minimum Load Current | 0.15 A |
| Number of Poles | 1 |
| Terminal Type | Screw |
| | |



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

| | |
|-------------------------------|--|
| Output Device | SCR |
| Load Voltage Range | 24 - 280V ac |
| Series | CKR24 |
| Maximum Turn On Time | 1/2 cycle |
| Dimensions | 81.9 x 22.5 x 99mm |
| Maximum Operating Temperature | +80°C |
| Length | 81.9mm |
| Off State Leakage Current | 10 mArms |
| Depth | 22.5mm |
| Operating Temperature Range | -40 - +80°C |
| Standards Met | CE, cURus |
| Special Features | AC or DC control, Zero-crossing (resistive loads) or Instantaneous-fire (inductive loads) output |
| Height | 99mm |
| Minimum Operating Temperature | -40°C |
| Capacitance | 8pF |



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com