



Industrial Automation Products & Solutions



i-Autoc KSI Series Solid State Relay, 25 A Load, Panel Mount, 280 V ac Load, 280 V ac Control

ผู้ผลิต : i-Autoc

รหัสสินค้า : KSI240A25-L

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	Panel Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	48 V ac
Minimum Control Voltage	90 V ac
Maximum Control Voltage	280 V ac
Switching Type	Zero Cross
Control Voltage Range	90 - 280 V ac
Terminal Type	Screw
Output Device	SCR, Triac
Relay Type	Industrial Single Phase Relay
Series	KSI
Maximum Turn On Time	20ms
Load Voltage Range	48 - 280V ac
Dimensions	58.6 x 45.7 x 26.5mm
Minimum Operating Temperature	-30°C
Maximum Operating Temperature	+80°C



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Operating Temperature Range	-30 - +80°C
Standards Met	CE, TUV, UL
Special Features	Internal MOV, Internal RC, LED Indication, Superior Thermal Performance, TVS Protection Circuit as Option
Depth	45.7mm
Length	58.6mm
Height	26.5mm
Off State Leakage Current	5 mA



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com