



## Industrial Automation Products & Solutions



### Celduc SUL9-SUM9 Series Solid State Relay, 32 A Load, DIN Rail Mount, 600 V ac Load, 32 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SUL965460

## Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	32 A
Mounting Type	DIN Rail
Maximum Load Voltage	600 V ac
Minimum Load Voltage	24 V ac
Minimum Control Voltage	3.5 V dc
Maximum Control Voltage	32 V dc
Switching Type	Zero Cross
Control Voltage Range	3.5 - 32 V dc
Minimum Load Current	5 mA
Range	SUL9
Number of Poles	1
Terminal Type	Screw
Output Device	Thyristor
Relay Type	AC



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Series	SUL9-SUM9
Load Voltage Range	24 - 600V ac
Maximum Turn On Time	10ms
Dimensions	22.5 x 119.1 x 80mm
Length	22.5mm
Maximum Operating Temperature	+100°C
Minimum Operating Temperature	-55°C
Standards Met	CE, cURus 100kA, EAC
Special Features	Zero Cross Solid State Relay Especially Designed for Resistive Loads, Yellow LED Visualization on The Input, IP20 Protection By Removable Flaps on Terminals with Optional Labels
Depth	119.1mm
Operating Temperature Range	-55 - +100°C
Height	80mm
Off State Leakage Current	1 mA



LINE OA  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com