



Industrial Automation Products & Solutions



RS PRO 3 Phase LCD Energy Meter, Type Energy Meter

ผู้ผลิต : RS PRO

รหัสสินค้า : 264-1010

Specifications

คุณลักษณะ	รายละเอียด
Cutout Width	91.5mm
Cutout Height	91.5mm
Display Type	LCD
Number of Digits	8
Number of Phases	3
Communication Port Type	Modbus RS485
Number of Inputs	3 x (Current Transformers) 3 x (Voltage) and Neutral
Number of Outputs	1 (Pulse)
Pulse Output	Yes
Depth	50mm
Digit Height	11.2 mm
Meter Accuracy	$\hat{A}\pm 0.5$ (Current) %, $\hat{A}\pm 0.5$ (Voltage) %, $\hat{A}\pm$ Class B (Active Energy)
Minimum Temperature	-20°C
Maximum Temperature	+55°C
Meter Type	Energy Meter
Measurement Range	19-519 (Phase) V ac, 47-63Hz, 10 mA-5A, 11-300 (Phase and Neutral)V ac
Maximum Measurement	519 (Phase) V ac, 300 (Phase and Neutral) V ac, 6A,63 Hz




บริษัท ทีเอส โซลูชัน จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Approvals	IEC/EN62053-21, IEC/EN50470-3, IEC/EN62053-23, IEC/EN50470, IEC/EN61326-1, IEC/EN55011 Class A, IEC/EN61000-4-2, IEC/EN61000-4-3, IEC/EN61000-4-4, IEC/EN61000-4-5, IEC/EN61000-4-6, IEC/EN61000-4-8, IEC/EN61000-4-11, IEC/EN50470-1/3, IEC/EN61010
Minimum Measurement	19 (Phase) V ac, 11 (Phase and Neutral) V ac, 47 Hz, 10mA



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com