



Industrial Automation Products & Solutions



RS PRO Straight Female 5 way M12 to Unterminated Sensor Actuator Cable, 5m

ผู้ผลิต : RS PRO

รหัสสินค้า : 174-7852

Specifications

| คุณลักษณะ | รายละเอียด |
|--------------------------------|----------------------|
| Number of Cores | 5 |
| Cross Sectional Area | 0.34 mm ² |
| Length | 5m |
| Sheath Colour | Black |
| Sheath Material | PUR |
| Connector 1 | M12 |
| Connector 1 Gender | Female |
| Connector 1 Number of Contacts | 5 |
| Connector 1 Orientation | Straight |
| Connector 2 | Unterminated |
| Shielded/Unshielded | Unshielded |
| Voltage Rating | 125 V ac/dc |
| Current Rating | 4 A |
| IP Rating | IP65, IP66K, IP67 |
| Fire Behaviour | Flame Retardant |
| Conductor Material | Copper |
| Insulation Material | PP |
| Minimum Bend Radius | 10 x 15 mm |



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

| | |
|-------------------------------|---|
| American Wire Gauge | 22 AWG |
| Oil Resistant | Yes |
| Cable Shape | Round |
| Standards Met | cLus Certified, CSA, cULus, DIN VDE 0298-4, EN 60529, IEC 60664-1, UL |
| Maximum Operating Temperature | +85°C |
| Minimum Operating Temperature | -25°C |
| Operating Temperature Range | -25 - +85 °C |
| Connector 1 Housing Gender | Female |
| Outer Diameter | 15mm |



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com