



## Industrial Automation Products & Solutions



### Phoenix Contact Straight Female 8 way M12 to Underminated Sensor Actuator Cable, 2m

ผู้ผลิต : Phoenix Contact

รหัสสินค้า : 1406105

## Specifications

| คุณลักษณะ                      | รายละเอียด                 |
|--------------------------------|----------------------------|
| Series                         | SAC-8P- 2.0-542/ FS SCO BK |
| Cross Sectional Area           | 0.25 mm <sup>2</sup>       |
| Number of Cores                | 8                          |
| Sheath Material                | PVC                        |
| Length                         | 2m                         |
| Sheath Colour                  | Yellow                     |
| Connector 1 Gender             | Female                     |
| Connector 1 Number of Contacts | 8                          |
| Connector 1 Orientation        | Straight                   |
| Connector 1                    | M12                        |
| Connector 2                    | Unterminated               |
| Coding                         | A                          |
| Shielded/Unshielded            | Unshielded                 |
| Voltage Rating                 | 30 V                       |
| Current Rating                 | 2 A                        |
| IP Rating                      | IP65, IP67, IP68           |
| Insulation Material            | PVC                        |
| Conductor Resistance           | 79.7 O/km                  |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                |
|-------------------------------|--------------------------------|
| American Wire Gauge           | 24 AWG                         |
| Outer Diameter                | 5.7mm                          |
| Connector 1 Housing Gender    | Female                         |
| Maximum Operating Temperature | +80°C                          |
| Conductor Material            | Tinned Copper                  |
| Minimum Bend Radius           | 44/ 8 x D mm                   |
| Minimum Operating Temperature | -5(Flexible) °C, -40(Fixed) °C |
| Standards Met                 | cUL, EAC, IEC 61076-2-101, UL  |
| Fire Behaviour                | Flame Retardant                |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com