



## Industrial Automation Products & Solutions



### TE Connectivity Straight Female 5 way M12 to Underminated Sensor Actuator Cable, 200mm

ผู้ผลิต : TE Connectivity

รหัสสินค้า : T4171310405-001

## Specifications

| คุณลักษณะ                      | รายละเอียด           |
|--------------------------------|----------------------|
| Series                         | T417                 |
| Number of Cores                | 5                    |
| Cross Sectional Area           | 0.34 mm <sup>2</sup> |
| Sheath Material                | PVC                  |
| Length                         | 200mm                |
| Connector 1 Number of Contacts | 5                    |
| Connector 1 Orientation        | Straight             |
| Connector 1 Gender             | Female               |
| Connector 1                    | M12                  |
| Connector 2                    | Underminated         |
| Coding                         | B                    |
| Mounting Type                  | Panel Mount          |
| Shielded/Unshielded            | Unshielded           |
| Current Rating                 | 4 A                  |
| Voltage Rating                 | 60 V ac/dc           |
| IP Rating                      | IP67                 |
| Conductor Material             | Copper               |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                |
|-------------------------------|--------------------------------|
| Operating Temperature Range   | -40 - +85 °C                   |
| American Wire Gauge           | 22 AWG                         |
| Insulation Material           | PVC                            |
| Connector 1 Housing Gender    | Female                         |
| Conductor Resistance          | $\leq 10 \text{ m}\Omega$      |
| Fire Behaviour                | Self-extinguishing             |
| Maximum Operating Temperature | +85°C                          |
| Cable Shape                   | Multicore                      |
| Standards Met                 | IEC 61076-2-101, UL, UL 94 V-0 |
| Minimum Operating Temperature | -40°C                          |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com