



## Industrial Automation Products & Solutions



### Sick Straight Female 4 way M12 to Straight Male 4 way M12 Connector & Cable, 10m

ผู้ผลิต : Sick

รหัสสินค้า : YF2A14-100VB3M2A14

## Specifications

| คุณลักษณะ                      | รายละเอียด             |
|--------------------------------|------------------------|
| Series                         | YF2A14                 |
| Cross Sectional Area           | 0.34 mm <sup>2</sup>   |
| Number of Cores                | 4                      |
| Sheath Colour                  | Black                  |
| Length                         | 10m                    |
| Sheath Material                | Polyvinyl Chloride PVC |
| Connector 1                    | M12                    |
| Connector 1 Gender             | Female                 |
| Connector 1 Number of Contacts | 4                      |
| Connector 1 Orientation        | Straight               |
| Connector 2 Housing Gender     | Male                   |
| Connector 2                    | M12                    |
| Connector 2 Gender             | Male                   |
| Connector 2 Orientation        | Straight               |
| Connector 2 Number of Contacts | 4                      |
| Coding                         | A                      |
| Shielding                      | Unshielded             |
| Shielded/Unshielded            | Unshielded             |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                   |
|-------------------------------|-------------------|
| Voltage Rating                | 250 V ac/dc       |
| Current Rating                | 4 A               |
| IP Rating                     | IP65, IP66K, IP67 |
| Standards Met                 | CE                |
| Minimum Operating Temperature | -5°C              |
| Outer Diameter                | 5mm               |
| American Wire Gauge           | 22 AWG            |
| Minimum Bend Radius           | 50 mm             |
| Connector 1 Housing Gender    | Female            |
| Operating Temperature Range   | -5 - 80 °C        |
| Maximum Operating Temperature | +80°C             |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com