



## Industrial Automation Products & Solutions



### Sick Straight Female 4 way M8 to Straight Male 4 way M8 Connector & Cable, 3m

ผู้ผลิต : Sick

รหัสสินค้า : YF8U14-030VA3M8U14

## Specifications

| คุณลักษณะ                      | รายละเอียด             |
|--------------------------------|------------------------|
| Series                         | YF8U14                 |
| Number of Cores                | 4                      |
| Cross Sectional Area           | 0.25 mm <sup>2</sup>   |
| Length                         | 3m                     |
| Sheath Material                | Polyvinyl Chloride PVC |
| Sheath Colour                  | Grey                   |
| Connector 1 Gender             | Female                 |
| Connector 1 Number of Contacts | 4                      |
| Connector 1                    | M8                     |
| Connector 1 Orientation        | Straight               |
| Connector 2                    | M8                     |
| Connector 2 Orientation        | Straight               |
| Connector 2 Number of Contacts | 4                      |
| Connector 2 Gender             | Male                   |
| Connector 2 Housing Gender     | Male                   |
| Coding                         | A                      |
| Mounting Type                  | Plug-In                |
| Shielding                      | Unshielded             |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

| Shielded/Unshielded           | Unshielded        |
|-------------------------------|-------------------|
| Current Rating                | 4 A               |
| Voltage Rating                | 1.5 kV            |
| IP Rating                     | IP65, IP66K, IP67 |
| Maximum Operating Temperature | +80°C             |
| Cable Shape                   | Round             |
| Oil Resistant                 | Yes               |
| Standards Met                 | UL                |
| American Wire Gauge           | 24                |
| Minimum Operating Temperature | -5°C              |
| Outer Diameter                | 4.8mm             |
| Connector 1 Housing Gender    | Female            |
| Fire Behaviour                | Flame Retardant   |
| Operating Temperature Range   | -5 - 80 °C        |
| Minimum Bend Radius           | 48 mm             |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com