



## Industrial Automation Products & Solutions



### Phoenix Contact PLC-RSC-230UC/21 Series Interface Relay, DIN Rail Mount, 230V ac/dc Coil, SPDT, 1-Pole

ผู้ผลิต : Phoenix Contact

รหัสสินค้า : 2966207

## Specifications

| คุณลักษณะ                     | รายละเอียด                |
|-------------------------------|---------------------------|
| Coil Voltage                  | 230V ac/dc                |
| Contact Configuration         | SPDT                      |
| Mounting Type                 | DIN Rail                  |
| Number of Poles               | 1                         |
| Minimum Input Voltage         | 179.4V ac                 |
| Maximum Input Voltage         | 230V ac                   |
| Switching Voltage             | 250V ac/dc                |
| Terminal Type                 | Screw                     |
| Depth                         | 6.2mm                     |
| Height                        | 94mm                      |
| Length                        | 80mm                      |
| Series                        | PLC-RSC-230UC/21          |
| Contact Material              | Silver Alloy              |
| Input Current                 | (dc) 3 mA, (ac) 3.2mA     |
| Accessory Type                | Relay Module              |
| Special Features              | Degree of protection IP20 |
| Minimum Operating Temperature | -40°C                     |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                                |                            |
|--------------------------------|----------------------------|
| Maximum Operating Temperature  | +55°C                      |
| Input Voltage Range            | 179.4 - 264.5V ac          |
| Relay Type                     | Solid State Relay          |
| Relay Switching Classification | Miniature Relay            |
| Dimensions                     | 80 x 6.2 x 94mm            |
| Turn Off Time                  | 15ms                       |
| Turn On Time                   | 7ms                        |
| Life                           | 2 x 10 <sup>7</sup> Cycles |
| Operating Temperature Range    | -40 - +55°C                |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com