




## Industrial Automation Products & Solutions



### Finder 48 Series Interface Relay, DIN Rail Mount, 110V ac Coil, SPDT, 1-Pole, 10A Load

ผู้ผลิต : Finder

รหัสสินค้า : 48.P3.8.110.0060SPA

## Specifications

| คุณลักษณะ                     | รายละเอียด           |
|-------------------------------|----------------------|
| Coil Voltage                  | 110V ac              |
| Contact Configuration         | SPDT                 |
| Mounting Type                 | DIN Rail             |
| Number of Poles               | 1                    |
| Load Current Rating           | 10A                  |
| Minimum Input Voltage         | 250V ac              |
| Maximum Input Voltage         | 400V ac              |
| Switching Voltage             | 250 V ac - 400V ac   |
| Terminal Type                 | Push In              |
| Depth                         | 75.3mm               |
| Height                        | 95.5mm               |
| Length                        | 15.8mm               |
| Series                        | 48 Series            |
| Contact Material              | Silver Alloy         |
| Input Current                 | 10.1mA               |
| Maximum Operating Temperature | +70°C                |
| Turn On Time                  | (dc) 12 ms, (ac) 7ms |
| Dimensions                    | 15.8 x 75.3 x 95.5mm |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                                |                                                                                                                          |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Operating Temperature Range    | -40 - +70°C                                                                                                              |
| Turn Off Time                  | (dc) 12 ms, (ac) 4ms                                                                                                     |
| Minimum Operating Temperature  | -40°C                                                                                                                    |
| Special Features               | AC Coils or DC Sensitive Coils, Identification Label, Supply Status Indication & EMC Coil Suppression Module as Standard |
| Standards Met                  | CE, CSA, CULus, EAC, EZU, GOST, IMQ, LCIE, Lloyds Register, RINA, VDE                                                    |
| Relay Switching Classification | General Purpose Relay                                                                                                    |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com