




Industrial Automation Products & Solutions



Panasonic Surface Mount Signal Relay, 12V dc Coil, 3A Switching Current, SPST

ผู้ผลิต : Panasonic

รหัสสินค้า : DS1E-M-DC12V

Overview

Panasonic Surface Mount Signal Relay รุ่น DS1E-M-DC12V คอยล์ 12V dc, การติดต่อแบบ SPST, สวิตช์กระแสสูงสุด 3A, สำหรับการติดตั้งแบบ Surface Mount

Features

- Coil Voltage: 12V dc
- Contact Configuration: SPST
- Mounting Type: Surface Mount (PCB Pin)
- Maximum Switching Current DC: 3 A
- Maximum Switching Voltage AC: 250V ac
- Maximum Switching Voltage DC: 220V dc
- Maximum Switching Power DC: 60 W
- Maximum Switching Power AC: 125VA
- Coil Resistance: 360Ω
- Coil Power: 400mW
- Isolation Coil To Contact: 1.5kV rms
- Electrical Life: 5000000 Operation Cycles
- Mechanical Life: 10⁷ Operations (ตามข้อมูล Life)
- Operating Temperature Range: -40 ถึง +70°C
- Contact Material: Gold Plated
- Features (จากสเปค): Suitable For Use In Difficult Environments; Gold Clad Twin Contacts Ensure High Reliability; Can Be Used With Automatic Solder And Automatic Wash Systems
- Dimensions: 20 x 9.9 x 9.9mm
- Terminal Type: PCB Pin
- Number of Poles: 1

Applications



- General Purpose
- Office Equipment
- Safety
- Telecommunications

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	12V dc
Contact Configuration	SPST
Mounting Type	Surface Mount
Maximum Switching Current DC	3 A
Maximum Switching Voltage AC	250V ac
Maximum Switching Voltage DC	220V dc
Series	DS
Maximum Switching Power DC	60 W
Length	20mm
Latching	No
Depth	9.9mm
Height	9.4mm
Dimensions	20 x 9.9 x 9.9mm
Terminal Type	PCB Pin
Number of Poles	1
Switching Current	3A
Application	General Purpose, Office Equipment, Safety, Telecommunications
Coil Resistance	360Ω
Maximum Switching Power AC	125VA
Contact Material	Gold Plated
Coil Power	400mW
Isolation Coil To Contact	1.5kV rms
Maximum Operating Temperature	+70°C



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Minimum Operating Temperature	-40°C
Electrical Life	5000000 Operation Cycles
Operating Temperature Range	-40 - +70°C
Features	Suitable For Use In Difficult Environments, Gold Clad Twin Contacts Ensure High Reliability, Can Be Used With Automatic Solder And Automatic Wash Systems
Life	10 ⁷ (Mechanical) Operations, 5 x 10 ⁵ (Electrical) Operations



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com