



Industrial Automation Products & Solutions



TE Connectivity Surface Mount Signal Relay, 24V dc Coil, 1A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : V23026D1024B201

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	24V dc
Contact Configuration	DPDT
Mounting Type	Surface Mount
Maximum Switching Current DC	1 A
Maximum Switching Voltage AC	150V ac
Maximum Switching Voltage DC	125V dc
Series	Axicom P1
Maximum Switching Power DC	30 W
Latching	No
Length	13.5mm
Depth	7.2mm
Height	8mm
Dimensions	14 x 8 x 7.8mm
Terminal Type	Surface Mount
Switching Current	1A
Number of Poles	1
Minimum Operating Temperature	-40°C
Coil Power	128mW



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Operating Temperature Range	-40 - +85°C
Features	Immersion Cleanable, Directly Trigger able With TTL Standard Modules
Isolation Coil To Contact	1.5kV rms
Maximum Switching Power AC	37.5VA
Coil Resistance	4500Ω@
Maximum Operating Temperature	+85°C
Contact Material	Gold Plated



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com