




Industrial Automation Products & Solutions



TE Connectivity PCB Mount Signal Relay, 3V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : 1462037-4

Overview

รีเลย์สัญญาณติด PCB แบบ IM series ขนาดบาง (slimline) โปรไฟล์ต่ำ 5.65mm ใช้พื้นที่บนบอร์ดน้อย เหมาะสำหรับการออกแบบที่มีข้อจำกัดด้านความสูงและพื้นที่ผิวบอร์ด

Features

- Coil Voltage: 3V dc
- Contact Configuration: DPDT (2 poles)
- Mounting Type: PCB Mount (Through Hole)
- Maximum Switching Current DC: 2 A
- Maximum Switching Voltage AC: 250V ac
- Maximum Switching Voltage DC: 220V dc
- Maximum Switching Power DC: 60 W
- Maximum Switching Power AC: 62.5 VA
- Dimensions: 10 x 6 x 5.65mm (Length x Depth x Height)
- โปรไฟล์ต่ำ (Height ~5.65mm)
- Non-Latching Relay (ไม่ลatching)
- Coil Power: 140mW
- Coil Resistance: 64Ω
- Isolation Coil To Contact: 1.8kV rms
- Contact Material: Gold Plated
- Operating Temperature Range: -40 - +85°C
- Life: Mechanical 100000000 Operations, Electrical 500000 Operations
- Features: Bifurcated Contacts, Low Coil Power Consumption
- Standards Met: UL

Applications

- Access & Transmission Equipment



- Automotive Applications
- Consumer Electronics
- HVAC
- Industrial Controls
- Measurement & Test Equipment
- Medical Equipment
- Modems
- Office & Business Equipment
- Optical Network Terminals
- Telecommunication

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	3V dc
Contact Configuration	DPDT
Mounting Type	PCB Mount
Maximum Switching Current DC	2 A
Maximum Switching Voltage AC	250V ac
Maximum Switching Voltage DC	220V dc
Series	IM
Maximum Switching Power DC	60 W
Length	10mm
Latching	No
Depth	6mm
Height	5.2mm
Dimensions	10 x 6 x 5.65mm
Terminal Type	Through Hole
Application	Access & Transmission Equipment, Automotive Applications, Consumer Electronics, HVAC, Industrial Controls, Measurement & Test Equipment, Medical Equipment, Modems, Office & Business Equipment, Optical Network Terminals, Telecommunication
Number of Poles	2
Switching Current	2A



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Life	1000000000 (Mechanical) Operations, 500000 (Electrical) Operations
Coil Power	140mW
Relay Switching Classification	Non-Latching Relay
Features	Bifurcated Contacts, Low Coil Power Consumption
Isolation Coil To Contact	1.8kV rms
Operating Temperature Range	-40 - +85°C
Contact Material	Gold Plated
Standards Met	UL
Minimum Operating Temperature	-40°C
Maximum Switching Power AC	62.5VA
Coil Resistance	64Î©
Maximum Operating Temperature	+85°C



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com