




## Industrial Automation Products & Solutions



### Omron Surface Mount Signal Relay, 24V dc Coil, 1A Switching Current, DPDT

ผู้ผลิต : Omron

รหัสสินค้า : G6K-2F-Y 24DC

## Specifications

| คุณลักษณะ                    | รายละเอียด        |
|------------------------------|-------------------|
| Coil Voltage                 | 24V dc            |
| Contact Configuration        | DPDT              |
| Mounting Type                | Surface Mount     |
| Maximum Switching Current DC | 1 A               |
| Maximum Switching Voltage AC | 125V ac           |
| Maximum Switching Voltage DC | 60V dc            |
| Series                       | G6K               |
| Maximum Switching Power DC   | 30 W              |
| Length                       | 10mm              |
| Latching                     | No                |
| Depth                        | 6.5mm             |
| Height                       | 5.2mm             |
| Dimensions                   | 10 x 6.5 x 5.2mm  |
| Terminal Type                | Surface Mount     |
| Switching Current            | 1A                |
| Number of Poles              | 2                 |
| Application                  | Signal            |
| Electrical Life              | 100000 Operations |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------|
| Life                          | 100000 (Electrical) cycles                                                       |
| Features                      | Low Dimension And Weight Combines To Improve Mounting Efficiency, RoHS Complaint |
| Coil Resistance               | 5.22 k $\Omega$                                                                  |
| Coil Power                    | 100mW                                                                            |
| Maximum Switching Power AC    | 37.5 VA                                                                          |
| Operating Temperature Range   | -40 - +70°C                                                                      |
| Contact Material              | Gold Plated                                                                      |
| Isolation Coil To Contact     | 2kV rms                                                                          |
| Maximum Operating Temperature | +70°C                                                                            |
| Minimum Operating Temperature | -40°C                                                                            |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com