



Industrial Automation Products & Solutions



TE Connectivity PCB Mount Signal Relay, 5V dc Coil, 2A Switching Current, DPDT

ผู้ผลิต : TE Connectivity

รหัสสินค้า : V23079A2001B301

Specifications

คุณลักษณะ	รายละเอียด
Coil Voltage	5V dc
Contact Configuration	DPDT
Mounting Type	PCB Mount
Maximum Switching Current DC	2 A
Maximum Switching Voltage AC	250V
Maximum Switching Voltage DC	220V dc
Maximum Switching Power DC	60 W
Series	Axicom P2
Latching	No
Length	14.5mm
Depth	7.4mm
Height	9.8mm
Dimensions	14.5 x 9.8 x 7.2mm
Terminal Type	Through Hole
Switching Current	2A
Number of Poles	2
Maximum Operating Temperature	+85°C
Life	100000000 (Mechanical) Operations, 50000000 (Electrical)



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

	Operations
Contact Material	Gold Plated
Features	Bifurcated Contacts, Immersion cleanable
Operating Temperature Range	-40 - +85°C
Minimum Operating Temperature	-40°C
Isolation Coil To Contact	1.5kV rms
Coil Resistance	178Î©
Maximum Switching Power AC	62.5VA
Coil Power	140mW



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com