



Industrial Automation Products & Solutions



Omron G3RV-ST Series Solid State Interface Relay, 24 Vdc Control, 2 A Load, DIN Rail Mount

ผู้ผลิต : Omron

รหัสสินค้า : G3RV-ST500-AL DC24

Specifications

คุณลักษณะ	รายละเอียด
Maximum Control Voltage	24 Vdc
Maximum Load Current	2 A
Mounting Type	DIN Rail
Maximum Load Voltage	264 V ac
Minimum Control Voltage	21.6 V
Control Voltage Range	19.2 - 26.4 V
Switching Type	High-Speed
Contact Configuration	SPDT
Load Voltage Range	75 - 264V
Minimum Load Voltage	75 V ac
Terminal Type	Push In
Number of Poles	1
Input Current	12mA
Depth	87.1mm
Length	88mm
Height	90mm
Rise Time	3ms



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Minimum Load Current	100 mA
Output Device	TRIAC
Width	6.2mm
Series	G3RV-ST
Minimum Operating Temperature	-30°C
Package Style	Carton Box
Isolation Voltage	2500V
Range	G3RV
Dimensions	88 x 90 x 6.2mm
Off State Leakage Current	5 mA
Standards Met	CSA C22.2 No.14, EN 62314, IEC 60529, UL
Special Features	60% Space Saving, Easy Maintenance
Maximum Operating Temperature	+55°C
Maximum Turn On Time	3 ms
Operating Temperature Range	-30 - 55°C
Manufacturer Part No.	G3RV-ST500-AL DC24



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com