



Industrial Automation Products & Solutions



Celduc SUL9-SUM9 Series Solid State Relay, 35 A Load, DIN Rail Mount, 600 V ac Load, 32 V dc Control

ผู้ผลิต : Celduc

รหัสสินค้า : SUL967460

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	35 A
Mounting Type	DIN Rail
Maximum Load Voltage	600 V ac
Minimum Load Voltage	24 V ac
Maximum Control Voltage	32 V dc
Minimum Control Voltage	3.5 V dc
Switching Type	Zero Cross
Control Voltage Range	3.5 - 32 V dc
Minimum Load Current	5 mA
Range	SUL9
Number of Poles	1
Terminal Type	Screw
Output Device	Thyristor
Relay Type	AC
Maximum Turn On Time	10ms
Series	SUL9-SUM9
Load Voltage Range	24 - 600V ac



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	22.5 x 119.1 x 80mm
Height	80mm
Standards Met	CE, cURus 100kA, EAC
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	+100°C
Operating Temperature Range	-40 - +100°C
Length	22.5mm
Off State Leakage Current	1 mA
Special Features	Zero Cross Solid State Relay Especially Designed for Resistive Loads, Yellow LED Visualization on The Input, IP20 Protection By Removable Flaps on Terminals with Optional Labels
Depth	119.1mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com