



## Industrial Automation Products & Solutions



### Sensata Crydom CW48 Series Solid State Relay, 25 A Load, Panel Mount, 660 V ac Load, 48 V dc, 280 V ac Control

ผู้ผลิต : Sensata / Crydom

รหัสสินค้า : CWU4825P

## Specifications

| คุณลักษณะ                     | รายละเอียด                  |
|-------------------------------|-----------------------------|
| Maximum Load Current          | 25 A                        |
| Mounting Type                 | Panel Mount                 |
| Maximum Load Voltage          | 660 V ac                    |
| Minimum Load Voltage          | 48 V ac                     |
| Maximum Control Voltage       | 48 V dc, 280 V ac           |
| Minimum Control Voltage       | 20 V ac/dc                  |
| Switching Type                | Zero Cross                  |
| Control Voltage Range         | 20 - 280 V ac, 20 - 48 V dc |
| Minimum Load Current          | 0.15 A                      |
| Terminal Type                 | Screw                       |
| Output Device                 | SCR                         |
| Relay Type                    | Solid State Relay           |
| Load Voltage Range            | 48 - 660V ac                |
| Maximum Turn On Time          | 17 ms                       |
| Series                        | CW48                        |
| Dimensions                    | 45.7 x 33 x 58.4mm          |
| Maximum Operating Temperature | +80°C                       |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                                                                                    |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| Capacitance                   | 8pF                                                                                                |
| Depth                         | 33mm                                                                                               |
| Minimum Operating Temperature | -30°C                                                                                              |
| Length                        | 45.7mm                                                                                             |
| Off State Leakage Current     | 1 mA                                                                                               |
| Height                        | 58.4mm                                                                                             |
| Special Features              | LED Status Indicator, EMC Compliant To Level 3, Removable IP20 Touch Safe Cover, Epoxy Free Design |
| Operating Temperature Range   | -40 - +80°C                                                                                        |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com