



Industrial Automation Products & Solutions



Sensata Crydom PMP Series Solid State Relay, 50 A Load, Panel Mount, 530 V ac Load, 10 V dc Control

ผู้ผลิต : Sensata / Crydom

รหัสสินค้า : PMP4850W

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	50 A
Mounting Type	Panel Mount
Maximum Load Voltage	530 V ac
Minimum Load Voltage	345 V ac
Minimum Control Voltage	0 V dc
Maximum Control Voltage	10 V dc
Switching Type	Burst Fire Control, Phase Angle
Control Voltage Range	0<arrow/>10 V dc
Minimum Load Current	100mA rms
Range	NOVA22
Number of Poles	1
Terminal Type	Screw
Relay Type	Control Relay



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Series	PMP
Maximum Turn On Time	20 cycles
Load Voltage Range	345 - 530V ac
Dimensions	22.5 x 53.1 x 91.9mm
Minimum Operating Temperature	-25°C
Maximum Operating Temperature	+70°C
Off State Leakage Current	2.2mArms
Length	22.5mm
Height	91.9mm
Standards Met	CE, CSA C22.2 No. 14, cULus Recognised E116949, EMC Compliant, IEC, IEC 60068-2-27, IEC 60068-2-6, UL, UL 94 V-0
Operating Temperature Range	-25 - +70°C
Special Features	LED Multifunction Status Indicator
Depth	53.1mm
Capacitance	8pF



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com