



## Industrial Automation Products & Solutions



### i-Autoc KSI Series Solid State Relay, 60 A Load, Panel Mount, 530 V ac Load, 32 V dc Control

ผู้ผลิต : i-Autoc

รหัสสินค้า : KSI480D60-L(068)

## Specifications

| คุณลักษณะ                   | รายละเอียด                    |
|-----------------------------|-------------------------------|
| Maximum Load Current        | 60 A                          |
| Mounting Type               | Panel Mount                   |
| Maximum Load Voltage        | 530 V ac                      |
| Minimum Load Voltage        | 48 V ac                       |
| Maximum Control Voltage     | 32 V dc                       |
| Minimum Control Voltage     | 4 V dc                        |
| Switching Type              | Zero Cross                    |
| Control Voltage Range       | 4 - 32 V dc                   |
| Terminal Type               | Screw                         |
| Output Device               | SCR                           |
| Relay Type                  | Industrial Single Phase Relay |
| Load Voltage Range          | 48 - 530V ac                  |
| Maximum Turn On Time        | 1ms                           |
| Series                      | KSI                           |
| Dimensions                  | 58.6 x 45.7 x 26.5mm          |
| Operating Temperature Range | -30 - +80°C                   |
| Length                      | 58.6mm                        |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                                                                                                             |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Depth                         | 45.7mm                                                                                                                      |
| Minimum Operating Temperature | -30°C                                                                                                                       |
| Special Features              | DBC Substrate for Superior Thermal Performance, Internal MOV, Internal RC, LED Indication, TVS Protection Circuit as Option |
| Standards Met                 | CE, TUV, UL                                                                                                                 |
| Maximum Operating Temperature | +80°C                                                                                                                       |
| Height                        | 26.5mm                                                                                                                      |
| Off State Leakage Current     | 3 mA                                                                                                                        |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com