



## Industrial Automation Products & Solutions



### Carlo Gavazzi RA 24 Series Solid State Relay, 50 A Load, Panel Mount, 280 V ac Load, 280V ac/dc Control

ผู้ผลิต : Carlo Gavazzi

รหัสสินค้า : RA2450HA06

## Specifications

| คุณลักษณะ               | รายละเอียด           |
|-------------------------|----------------------|
| Maximum Load Current    | 50 A                 |
| Mounting Type           | Panel Mount          |
| Maximum Load Voltage    | 280 V ac             |
| Minimum Load Voltage    | 24 V ac              |
| Minimum Control Voltage | 90V ac/dc            |
| Maximum Control Voltage | 280V ac/dc           |
| Switching Type          | Zero                 |
| Control Voltage Range   | 90 - 280 V ac/dc     |
| Minimum Load Current    | 250 mA               |
| Number of Poles         | 1                    |
| Terminal Type           | Screw                |
| Output Device           | Varistor             |
| Relay Type              | Solid State Relay    |
| Load Voltage Range      | 24 - 280V ac         |
| Maximum Turn On Time    | 1 s                  |
| Series                  | RA 24                |
| Dimensions              | 44.5 x 57.8 x 24.5mm |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                                                        |
|-------------------------------|------------------------------------------------------------------------|
| Capacitance                   | 8pF                                                                    |
| Maximum Operating Temperature | +70°C                                                                  |
| Depth                         | 57.8mm                                                                 |
| Length                        | 44.5mm                                                                 |
| Off State Leakage Current     | 3 mA                                                                   |
| Special Features              | AC Solid State Relay, Zero Switching, Direct Copper Bonding Technology |
| Height                        | 29mm                                                                   |
| Minimum Operating Temperature | -20°C                                                                  |
| Operating Temperature Range   | -20 - +70°C                                                            |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com