



Industrial Automation Products & Solutions



Schneider Electric Harmony Relay Series Solid State Relay, 2 A Load, PCB Mount, 280 V ac Load, 12 V dc Control

ผู้ผลิต : Schneider Electric

รหัสสินค้า : SSL1A12JD

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	2 A
Mounting Type	PCB Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	24 V ac
Minimum Control Voltage	3 V dc
Maximum Control Voltage	12 V dc
Switching Type	AC
Control Voltage Range	3 - 12 V dc
Minimum Load Current	0.07 A
Number of Poles	1
Terminal Type	PCB Pin
Contact Configuration	SPST
Output Device	SCR
Relay Type	Single Phase
Load Voltage Range	24 - 280V ac
Series	Harmony Relay
Maximum Turn On Time	1/2 cycle



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Dimensions	28 x 5 x 15mm
Better World Product	Yes
Better World Verification	Green Premium
Length	28mm
Off State Leakage Current	4 mA
Height	15mm
Operating Temperature Range	-20 - +80°C
Depth	5mm
Capacitance	1.5pF
Standards Met	CE, CSA, UL
Special Features	Built-In Diode Protection Circuit & LED Indicator, Mounted on Universal AC/DC Sockets, Slim Interface SSL Relays with PCB Terminals



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com