



## Industrial Automation Products & Solutions



### Sensata Crydom H12WD Series Solid State Relay, 90 A Load, Panel Mount, 660 V rms Load, 32 V dc Control

ผู้ผลิต : Sensata / Crydom

รหัสสินค้า : H12WD4890-10

## Specifications

| คุณลักษณะ               | รายละเอียด           |
|-------------------------|----------------------|
| Maximum Load Current    | 90 A                 |
| Mounting Type           | Panel Mount          |
| Maximum Load Voltage    | 660 V rms            |
| Minimum Load Voltage    | 48 V rms             |
| Maximum Control Voltage | 32 V dc              |
| Minimum Control Voltage | 4 V dc               |
| Switching Type          | Instantaneous        |
| Control Voltage Range   | 4 - 32 V dc          |
| Minimum Load Current    | 150 mA rms           |
| Terminal Type           | Screw                |
| Output Device           | SCR                  |
| Relay Type              | Solid State Relay    |
| Maximum Turn On Time    | 1/2 ms               |
| Series                  | H12WD                |
| Load Voltage Range      | 48 - 660Vrms         |
| Dimensions              | 45.7 x 19.8 x 58.4mm |
| Capacitance             | 8pF                  |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------|
| Depth                         | 19.8mm                                                                                |
| Maximum Operating Temperature | +80°C                                                                                 |
| Off State Leakage Current     | 1 mA rms                                                                              |
| Special Features              | SCR Output For Heavy Industrial Loads, Redesigned Housing With Anti Rotation Barriers |
| Operating Temperature Range   | -40 - +80°C                                                                           |
| Length                        | 45.7mm                                                                                |
| Minimum Operating Temperature | -40°C                                                                                 |
| Height                        | 58.4mm                                                                                |



LINE OA  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com