



Industrial Automation Products & Solutions



i-Autoc KSI Series Solid State Relay, 25 A Load, Panel Mount, 280 V ac Load, 32 V dc Control

ผู้ผลิต : i-Autoc

รหัสสินค้า : KSI240D25-L(068)

Specifications

คุณลักษณะ	รายละเอียด
Maximum Load Current	25 A
Mounting Type	Panel Mount
Maximum Load Voltage	280 V ac
Minimum Load Voltage	48 V ac
Maximum Control Voltage	32 V dc
Minimum Control Voltage	4 V dc
Switching Type	Zero Cross
Control Voltage Range	4 - 32 V dc
Terminal Type	Screw
Output Device	SCR, Triac
Relay Type	Industrial Single Phase Relay
Series	KSI
Maximum Turn On Time	1ms
Load Voltage Range	48 - 280V ac
Dimensions	58.6 x 45.7 x 26.5mm
Maximum Operating Temperature	+80°C
Depth	45.7mm



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Off State Leakage Current	5 mA
Length	58.6mm
Operating Temperature Range	-30 - +80°C
Special Features	Internal MOV, Internal RC, LED Indication, Superior Thermal Performance, TVS Protection Circuit as Option
Standards Met	CE, TUV, UL
Minimum Operating Temperature	-30°C
Height	26.5mm



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com