



Industrial Automation Products & Solutions



Belden1503A Series 2 Core Line level Low Voltage signal Cable, 0.33 mm² CSA Screened, 3.61mm od, 304m, Red

ผู้ผลิต : Belden

รหัสสินค้า : 1503A 002U1000

Specifications

คุณลักษณะ	รายละเอียด
Audio Cable Type	Line level Low Voltage signal Cable
Number of Cores	2
Cross Sectional Area	0.33 mm ²
Screened/Unscreened	Screened
Insulation Material	PVC
Outer Diameter	3.61mm
Length	304m
CPR Certification	Eca
Minimum Operating Temperature	-30°C
Maximum Operating Temperature	+90°C
Sheath Colour	Red
American Wire Gauge	22 AWG
Screen Type	Aluminium/PET Foil
Sheath Material	PVC
Characteristic Impedance	38 Î©
Number of Strands	7
Drain Wire	Yes



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Capacitance Core To Screen	318.16pF/m
Conductor Resistance	48.228348 $\hat{I}\text{C}/\text{km}$
Voltage Rating	300 V
Conductor Strand Type	Stranded
Conductor Material	Copper
Core Strands	7/30
Capacitance Core To Core	173.84pF/m
Cable Shape	Multicore
Current Rating	2.9 A
Series	1503A



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com