



Industrial Automation Products & Solutions



TE Connectivity Straight Female 4 way M12 to Straight Male 4 way M8 Sensor Actuator Cable, 1.5m

ผู้ผลิต : TE Connectivity

รหัสสินค้า : 1-2273109-4

Overview

TE Connectivity Straight Female 4 way M12 to Straight Male 4 way M8 Sensor Actuator Cable, 1.5m (รุ่น 1-2273109-4) ชุดสายเชื่อมต่อ M12 to M8 สำหรับงานเซนเซอร์และแอคทูเอเตอร์ ออกแบบเพื่อความเข้ากันได้และความน่าเชื่อถือ

สาย M12 (female) ถึง M8 (male) แบบตรง มี 4 คอนแทก ใช้วัสดุปลอก PVC ยาว 1.5 m ระบุคุณสมบัติไฟฟ้า Voltage 30 V ac/dc และ Current 4 A พร้อมมาตรฐานหลายรายการ (CSA, EN 60529, RoHS, UL) และช่วงอุณหภูมิการใช้งาน -30 ถึง +80 °C

Features

- Number of Cores: 4
- Cross Sectional Area: 0.34 mm²
- Sheath Colour: Black
- Length: 1.5m
- Sheath Material: PVC
- Connector 1: M12, Female, Straight, 4 contacts
- Connector 2: M8, Male, Straight, 4 contacts
- Coding: A
- Shielded/Unshielded: Unshielded
- Voltage Rating: 30 V ac/dc
- Current Rating: 4 A
- IP Rating: IP65, IP67
- Standards Met: CSA, EN 60529, RoHS Compliant, UL
- Operating Temperature Range: -30 - +80 °C
- American Wire Gauge: 22 AWG
- Outer Diameter: 4.8mm
- Minimum Bend Radius: 48 mm



Applications

- งานเซนเซอร์และอัตโนมัติ (ตามคำอธิบายสินค้า)
- การเชื่อมต่อระหว่างอุปกรณ์มีหัวต่อ M12 และ M8

Specifications

คุณลักษณะ	รายละเอียด
Number of Cores	4
Cross Sectional Area	0.34 mm ²
Sheath Colour	Black
Length	1.5m
Sheath Material	PVC
Connector 1	M12
Connector 1 Gender	Female
Connector 1 Orientation	Straight
Connector 1 Number of Contacts	4
Connector 2 Number of Contacts	4
Connector 2 Orientation	Straight
Connector 2 Housing Gender	Male
Connector 2 Gender	Male
Connector 2	M8
Coding	A
Shielded/Unshielded	Unshielded
Voltage Rating	30 V ac/dc
Current Rating	4 A
IP Rating	IP65, IP67
Standards Met	CSA, ELV Compliant, EN 60529, RoHS Compliant, UL
Minimum Operating Temperature	-30°C
American Wire Gauge	22 AWG



บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Outer Diameter	4.8mm
Connector 1 Housing Gender	Female
Operating Temperature Range	-30 - +80 °C
Maximum Operating Temperature	+80°C
Minimum Bend Radius	48 mm
Insulation Material	PVC
Cable Shape	Multicore



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com