



## Industrial Automation Products & Solutions



### Sick Straight Female 8 way M12 to Straight Male 8 way M12 Connector & Cable, 600mm

ผู้ผลิต : Sick

รหัสสินค้า : YF2A18-C60UA5M2A18

## Specifications

| คุณลักษณะ                      | รายละเอียด           |
|--------------------------------|----------------------|
| Series                         | YF2A18               |
| Number of Cores                | 8                    |
| Cross Sectional Area           | 0.25 mm <sup>2</sup> |
| Length                         | 600mm                |
| Sheath Material                | Polyurethane PUR     |
| Sheath Colour                  | Black                |
| Connector 1 Number of Contacts | 8                    |
| Connector 1 Gender             | Female               |
| Connector 1                    | M12                  |
| Connector 1 Orientation        | Straight             |
| Connector 2                    | M12                  |
| Connector 2 Orientation        | Straight             |
| Connector 2 Gender             | Male                 |
| Connector 2 Number of Contacts | 8                    |
| Connector 2 Housing Gender     | Male                 |
| Coding                         | A                    |
| Mounting Type                  | Plug-In              |
| Shielded/Unshielded            | Unshielded           |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                          |
|-------------------------------|--------------------------|
| Shielding                     | Unshielded               |
| Voltage Rating                | 800 V                    |
| Current Rating                | 2 A                      |
| IP Rating                     | IP65, IP66K, IP67        |
| Cable Shape                   | Round                    |
| Oil Resistant                 | Yes                      |
| Standards Met                 | IEC 60332-1, UL 1581 FT2 |
| American Wire Gauge           | 24                       |
| Outer Diameter                | 5.8mm                    |
| Minimum Operating Temperature | -25°C                    |
| Minimum Bend Radius           | 58 mm                    |
| Fire Behaviour                | Flame Retardant          |
| Maximum Operating Temperature | +80°C                    |
| Operating Temperature Range   | -25 - 80 °C              |
| Connector 1 Housing Gender    | Female                   |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com