



## Industrial Automation Products & Solutions



### Phoenix Contact Straight Male 4 way M12 to Unterminated Sensor Actuator Cable, 500mm

ผู้ผลิต : Phoenix Contact

รหัสสินค้า : 1419991

## Specifications

| คุณลักษณะ                      | รายละเอียด                |
|--------------------------------|---------------------------|
| Cross Sectional Area           | 0.34 mm <sup>2</sup>      |
| Number of Cores                | 4                         |
| Sheath Colour                  | Black, Blue, Brown, White |
| Sheath Material                | TPE                       |
| Length                         | 500mm                     |
| Connector 1 Gender             | Male                      |
| Connector 1                    | M12                       |
| Connector 1 Orientation        | Straight                  |
| Connector 1 Number of Contacts | 4                         |
| Connector 2                    | Unterminated              |
| Coding                         | A                         |
| Mounting Type                  | Panel Mount               |
| Shielded/Unshielded            | Unshielded                |
| Armoured                       | No                        |
| Shielding                      | Unshielded                |
| Current Rating                 | 4 A                       |
| Voltage Rating                 | 250 V                     |
| IP Rating                      | IP67                      |



## บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

|                               |                 |
|-------------------------------|-----------------|
| Standards Met                 | cUL, UL         |
| Cable Shape                   | 4 Twisted Cores |
| Fire Behaviour                | Flame Retardant |
| Maximum Operating Temperature | +80°C           |
| Connector 1 Housing Gender    | Male            |
| Operating Temperature Range   | -40 - +80 °C    |
| Number of Strands             | 4               |
| Conductor Material            | Tinned Copper   |
| Minimum Operating Temperature | -40°C           |
| Insulation Material           | TPE             |
| American Wire Gauge           | 22 AWG          |



**LINE OA**  
@thsolution

### Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

**Tel. :** 02-066-1996

**LINE OA :** @thsolution

**Website :** www.thsolution.com