



Industrial Automation Products & Solutions



Belden 8259 Series, 305m, RG58 Coaxial, Unterminated 50 Ω

ผู้ผลิต : Belden

รหัสสินค้า : 8259 0101000

Specifications

คุณลักษณะ	รายละเอียด
Terminated/Unterminated	Unterminated
Coaxial Type	RG58
Outer Diameter	4.9mm
CPR Certification	Eca
Characteristic Impedance	50 Ω
Attenuation	22.8 dB/100 ft @ 1000 MHz
Length	305m
Sheath Colour	Black
Conductor Strand Type	Stranded
Insulation Material	PE
Velocity ratio	66%
Conductor Material	Tinned Copper
Size of Strands	20 AWG
Minimum Operating Temperature	-30°C
Sheath Material	Polyvinyl Chloride PVC
Capacitance	101.05pF/m
Operating Temperature Range	-30 - +75 °C
Number of Strands	19




บริษัท ทีเอส โซลูชั่น จำกัด

27/66 ถนนรัชดา-รามอินทรา แขวงรามอินทรา เขตคันนายาว กรุงเทพมหานคร 10230

โทร : 02-066-1996 | Line OA : @thsolution | www.thsolution.com

Series	8259
Core Strands	1/0.89
Maximum Operating Temperature	+75°C
Standards Met	EU CE Mark, EU Directive 2000/53/EC (ELV), EU Directive 2003/96/EC (BFR), EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), EU Directive 2015/863/EU, EU Directive Compliance
Shielding	Tinned Copper Braid



LINE OA
@thsolution

Need a quotation or technical support?

ติดต่อทีมงาน THSolution สำหรับข้อมูลสินค้า ราคา สต็อกสินค้า

Tel. : 02-066-1996

LINE OA : @thsolution

Website : www.thsolution.com